



Safety Data Sheet

1 - Identification

Trade Name: WD-40 Specialist Superior Performance True Multi-Purpose Grease	Canadian Office: WD-40 Products [Canada] Ltd. P.O. Box 220 Toronto, Ontario M9C 4V3 Information Phone #: (416) 622-9881 Emergency Phone # 24 hr: Canutec: (613) 996-6666 - Designated for use only in the event of chemical emergencies involving a spill, leak, fire exposure or accident involving chemicals
Product Use: Lubricant, grease	
Restrictions on Use: None identified	
SDS Date Of Preparation: December 12, 2017	

2 – Hazards Identification

WHMIS 2015/GHS Classification:

Not Hazardous

Note: This product is a consumer product and is labeled in accordance with the Consumer Chemicals and Containers Regulations (CCCR) which take precedence over WHMIS 2015 labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Label Elements:

Not required

3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	WHMIS 2015/ GHS Classification
Petroleum Distillates	64741-88-4 64742-53-6 64742-65-0 64742-58-1 64742-62-7	45 - 70%	Not hazardous
Non-Hazardous Ingredients	Mixture	10 - 30%	Not hazardous
Calcium Sulfonate	61789-86-4	5 - <10%	Eye Irritant Category 2 Skin Irritant Category 2
Calcium Metaborate	Proprietary	1 - 5%	Eye Damage Category 1 Skin Irritant Category 2

4 – First Aid Measures

Ingestion (Swallowed): While aspiration is unlikely due to viscosity, do not induce vomiting. Rinse mouth with water. Call a physician, poison control center, or the WD-40 Safety Hotline at 1-888-324-7596.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for 15 minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation or rash develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Signs and Symptoms of Exposure: May cause mild eye and skin irritation. Prolonged or repeated skin contact may cause defatting dermatitis.

Indication of Immediate Medical Attention/Special Treatment Needed: Immediate medical attention is not required.

5 – Fire Fighting Measures

Suitable (and unsuitable) Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Specific Hazards Arising from the Chemical: Combustion will produce carbon oxides, sulfur oxides, smoke fumes and unburned hydrocarbons.

Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing in areas where chemicals are used and stored. Cool fire-exposed containers with water.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

Methods and Materials for Containment/Cleanup: Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Avoid breathing oil mists. Use with adequate ventilation. Keep away from heat, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

Conditions for Safe Storage: Store in a cool, well-ventilated area, away from incompatible materials. NFPA Class IIIB Liquid.

8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure limits
Petroleum Distillates	5 mg/m ³ (inhalable) TWA ACGIH TLV (as mineral oil) 5 mg/m ³ TWA, 10 mg/m ³ STEL Canada-Ontario (as oil mist, mineral) 5 mg/m ³ TWA, 10 mg/m ³ STEL Canada-Québec (as oil mist, mineral) 1 mg/m ³ TWA British Columbia (as Oil mist-mineral, severely refined)
Calcium Metaborate	None Established
Calcium sulfonate	None Established

The Following Controls are Recommended for Normal Consumer Use of this Product

Appropriate Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact.

Skin Protection: Avoid prolonged skin contact. Wash hands with soap and water after use.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety glasses recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

Appearance:	Blue colored grease	Flammable Limits:	Not established
Odor:	Pleasant odor	Vapor Pressure:	Not established
Odor Threshold:	Not established	Vapor Density:	Not established

pH:	Not applicable	Relative Density:	0.9 g/cm ³
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	>316°C (>600°F)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	>180°C (>356°F)	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Not applicable	Viscosity:	>21 cSt @ 40°C (104°F)
VOC:	Not established	Pour Point:	Not established

10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions

Chemical Stability: Stable

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Avoid heat, flames and other sources of ignition.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon oxides, sulfur oxides, smoke fumes and unburned hydrocarbons.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: High concentrations of oil mists may cause nasal and respiratory irritation.

Skin Contact: Direct contact may cause mild skin irritation. Prolonged and/or repeated contact may produce drying and defatting with possible dermatitis. While calcium sulfonate is classified as a skin sensitizer, testing has demonstrated that sensitization will not occur with mixtures containing less than 10%.

Eye Contact: Contact may be mildly irritating to eyes. May cause redness and tearing.

Ingestion: This product has low oral toxicity. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects: None expected.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg and the dermal toxicity greater than 2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria.

12 – Ecological Information

Ecotoxicity: No specific aquatic toxicity data is currently available; however components of this product are not expected to be harmful to aquatic organisms.

Persistence and Degradability: Components are not readily biodegradable.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available

Other Adverse Effects: None known

13 - Disposal Considerations

If this product becomes a waste, it would not be expected to meet the criteria of a RCRA of a hazardous waste. However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

14 – Transportation Information

DOT Surface Shipping Description: Not Regulated

Canadian TDG Classification: Not regulated
IMDG Shipping Description: Not Regulated
ICAO Shipping Description: Not Regulated

NOTE: WD-40 Company does not test containers to assure that they can withstand the pressure change without leakage when transported by air. We do not recommend that our products be transported by air unless a specific review is conducted.

15 – Regulatory Information

National Pollutant Release Inventory (NPRI): This product contains the following chemicals that are listed on the NPRI Substance List: None

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List, Canadian Non-Domestic Substances List, or exempt from notification.

16 – Other Information

HMIS Hazard Rating:

Health – 1 (moderate hazard), Fire Hazard – 1 (slight hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: February 15, 2018

Supersedes: December 12, 2017

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Reviewed by: I. Kowalski

Regulatory Affairs Department

1089300/No.0137103